

- 1 1/4 INCH WELDED CIRCULAR STEEL PLATE, 1/8 INCH MAXIMUM LIP.
- 2 3 INCH DIAMETER, 5 FEET LONG SCHEDULE 40 GALVANIZED PIPE.
- 3 PADLOCK (FURNISHED BY THE CITY).
- 4 INCH DIAMETER, 21 INCH LONG SCHEDULE 40 GALVANIZED PIPE.
- (5) 3/4 INCH STEEL PIN WITH 1/2 INCH HOLE FOR LOCK; PIN THROUGH 13/16 INCH HOLE IN 3 INCH BOLLARD AND 4 INCH SLEEVE.
- 6 ADJACENT CONCRETE SIDEWALK/ASPHALT CONCRETE.
- 7 CLASS "A" CONCRETE FOUNDATION, CENTERED ON BOLLARD.
- (8) 3" WIDE ORANGE/SILVER/ORANGE REFLECTIVE TAPE, 3M SERIES CW80.

NOTE:

A. BOLLARD AND SLEEVE TO BE PRIMERED AND PAINTED WITH 2 COATS OF HIGH GLOSS WHITE RUST INHIBITIVE PAINT.

THE CITY OF WEST SACRAMENTO - STANDARD DETAIL			
APPROVED BY: CITY ENGINEER C-38733 P.E. NO.	3/31/05 DATE	BOLLARD	EXE CITY OF
REVISION:		(REMOVABLE ONLY)	EST. 1987
REVISION:		SINGLE LOCK	A P
REVISION:		STANDARD STANDARD	WORAM E
REVISION:		DETAIL #: 240	DACKI